

MARKAL[®] PAINTSTIKS[®]

Markal[®] Paintstik[®] B







Qty 12

Features & Benefits

- Weather and UV-resistant
- Ideal for layout, colour coding, fabrication and identification
- Marking range: -46°C to 66°C



Markal[®] Paintstik[®] B

	Markal [®] Paintstik [®] B Black	34011201
	Markal [®] Paintstik [®] B Red	34011202
	Markal [®] Paintstik [®] B Blue	34011203
	Markal [®] Paintstik [®] B Yellow	34011205
	Markal [®] Paintstik [®] B Orange	34011206
	Markal [®] Paintstik [®] B White	34011211

Markal[®] Paintstik[®] B-L

Qty 12

Features & Benefits

- Designed for fabricating structural steel or layout work where the marks are required to bleed through a primer coat covering the marks
- Marking range: -46°C to 66°C



Markal[®] Paintstik[®] B-L

	Markal [®] Paintstik [®] B-L Blue	34061203
---	---	----------

Markal[®] Paintstik[®] H





Qty 144

Features & Benefits

- Bright colour range for higher visibility, ideal for marking hot coils, billets, slabs, bars and ingots
- Long-lasting, weather and fade resistant and marks will not run, char, discolour, peel or crack
- Marking range: 107°C to 593°C



Markal[®] Paintstik[®] H

	Markal [®] Paintstik [®] H Red	34024402
	Markal [®] Paintstik [®] H Blue	34024403
	Markal [®] Paintstik [®] H Yellow	34024405
	Markal [®] Paintstik [®] H White	34024411

Markal[®] Paintstik[®] K

Qty 12

Features & Benefits

- Marks on extremely hot steel and marks will not run, char, discolour, peel or crack
- Ideal for marking on iron and steel castings, ingots, forgings, blooms, billets and high-temperature metal alloys
- Marking range: 982°C to 1204°C



Markal[®] Paintstik[®] K

	Markal [®] Paintstik [®] K White	34081211
---	--	----------

Markal[®] Paintstik[®] P

Qty 12

Features & Benefits

- Designed for marking steel prior to the galvanising process
- Marks are completely removed in the pickling bath and will not interfere with the galvanising process
- Marking range: -46°C to 66°C



Markal[®] Paintstik[®] P

	Markal [®] Paintstik [®] P White	34061211
---	--	----------

