










# ZINC<sup>TM</sup> GUARD

## ZINC GUARD QUICK DRY ENAMEL Features & Benefits

- Quick drying top coat (touch dry in 10 – 15 minutes)
- Protect surfaces against rust whilst providing a durable finish
- Ideal for both interior and exterior projects
- Suitable for use on all metal surfaces such as: fences, gates, doors, letter boxes, fabricated steel, brackets, trailers, factory equipment and machinery

### Zinc Guard Quick Dry Enamel (Horizontal Spray)

|   |                   |       |    |           |
|---|-------------------|-------|----|-----------|
|  | Flat Black        | Flat  | 12 | 230932101 |
|  | Satin Black       | Satin | 12 | 230932201 |
|  | High Gloss Black  | Gloss | 12 | 230932301 |
|  | Signal Red R13    | Gloss | 12 | 230932302 |
|  | Ocean Blue        | Gloss | 12 | 230932303 |
|  | Brunswick Green   | Gloss | 12 | 230932304 |
|  | Golden Yellow Y14 | Gloss | 12 | 230932305 |
|  | Silver            | Gloss | 12 | 230932310 |
|  | High Gloss White  | Gloss | 12 | 230932311 |



### Suitable Surfaces

Pre painted metal surfaces, steel, wrought iron, galvanised iron and non-ferrous metal such as; aluminium, alloys, ZINCALUME® and stainless steel with appropriate primer



### Coverage

Approximately 2 sqm per aerosol can (depending on surface and colour used)



### Drying Time

Touch dry in 10–15 minutes.  
Recoat after 1 hour.



### Ideal Application Temperature

Between 10°C and 35°C

